

IDENTIV

MobilisID

Smart, Mobile Credential Access Control Solution



Identiv's MobilisID mobile credential system brings ease and simplicity to physical access and management without compromising security.

Using the latest in Bluetooth and capacitive technologies, MobilisID Readers allow the freedom to access a controlled environment without presenting credentials. For those sites that require support for legacy, proximity-based credentials (including cards, tags, or fobs), MobilisID supports 26-37bit 125kHz low frequency (LF) credentials, making the transition from physical to virtual-based access control seamless.

MobilisID is also cost-effective by cutting out production hardware and eliminating costs to deploy, ship, and track physical credentials.

The cloud-based MobilisID Manager works on any browser and makes issuing, updating, and removing credentials easy.

The MobilisID app, available on the Apple® App Store and Google® Play Store, converts almost any iOS or Android smartphone or tablet into a direct replacement for a traditional, physical credential. MobilisID securely transmits a personalized credential using the latest Bluetooth technology to the readers, allowing the user to freely move throughout a building or facility without the need to present the mobile device.

Physical Access via Mobile

- Mobile access with Bluetooth Low Energy (BLE) and legacy proximity credential support

Easy Management

- Cloud-based credential system simplifies issuing and managing credentials

Universal System Support

- Mobile credential system works with all access control systems that support Wiegand readers

Replaces Traditional Credentials

- App works with most Apple® and Android®-based devices

Flexible Installation Options

- Designed to mount in mullion or single-gang applications

MobilisID Specifications

Technology	125 kHz HID, AWID, Farpointe Data, CASI-RUSCO
Devices Supported	iOS: 11.0 or Later Android: 6.0 or Later supporting BLE Peripheral Mode
Mounting	Mullion or U.S single-gang (using included adapter plate)
Dimensions	6 in (15.2 cm) H x 1.7 in (4.3 cm) W x 1.3 in (3.3 cm) D
Certifications	FCC, Canada ISED, UL 294, and Bluetooth
Indoor/Outdoor Installation	Electronics potted and sealed with tamper-resistant epoxy
Current	75 mA typical at 12VDC 135-155 mA max at 12VDC
Voltage	+6V to 16V +12V is recommended
Interface	Wiegand 26-37 bit
Operating Temperature	-27° F to 150° F (-33° C to 66° C)
Color	Black with clear surface
Cabling	Wiegand 500 ft (152 m) 18 AWG wire
Audio	5 kHz buzzer

Ordering Information

MobilisID Bluetooth + Proximity Smart Reader 9020BBP0000	MobilisID Mullion Black Wiegand Reader. BLE and 125kHz credentials (ASK: Casi- Rusco & FSK: HID, Farpointe, AWID)
MobilisID Mobile Credential - Monthly Subscription MBID-M10	MobilisID - 10 Mobile Credentials for a single organization, Monthly Subscription
MobilisID Mobile Credential - Monthly Subscription MBID-M100	MobilisID - 100 Mobile Credentials for a single organization, Monthly Subscription
MobilisID Mobile Credential - Annual Subscription MBID-A10	MobilisID - 10 Mobile Credentials for a single organization, Annual Subscription
MobilisID Mobile Credential - Annual Subscription MBID-A100	MobilisID - 100 Mobile Credentials for a single organization, Annual Subscription
MobilisID One Single-Device Mobile Credential MBID-S	MobilisID Single-User, Single-Device Mobile Credential for the lifetime of that device. One-Time Installation.